



Tel: +27 11 900 3633

Cell: +27 633739195

Website: www.arrow-chem.co.za

Email: sales@thearrow.co.za

HC SOEKOE cc t/a ARROW CHEM

Reg No:2002/029572/23

Vat Reg No:4600249488

Date: 2025

Alrode South
Alberton
South Africa

TECHNICAL DATA SHEET

ALUBRITE

ALUMINIUM CLEANER

ALUBRITE is recommended for the cleaning of aluminium bodies of road vehicles. It is a liquid acid cleaner giving good penetration and is free rinsing. It removes difficult road soils and atmospheric dust and will also remove light oil films.

METHOD OF APPLICATION

The surface to be cleaned should first be hosed down with cold water and the solution of ALUBRITE applied to the surface while it is still wet. The dilution ratio should be 1:15 to 1:10 water depending upon the amount of oxidation soil and dirt to be removed. Rinse after 5-10 minutes with plenty of clean water. Do not allow to remain on the surface for periods longer than suggested.

USE DIRECTIONS

After cleaning, rinse down thorough with cold water.

SAFETY PRECAUTIONS AND FIRST AID

ALUBRITE contains strong mineral acids. Avoid contact with skin and eyes, in case of accidental contact rinse freely with water. avoid prolonged contact on metal surfaces and avoid contact with glass windscreens and windows.

EYES: In the case of accidental eye contact, rinse freely with water and obtain medical attention
SKIN: Wash off with water
INGESTION: Give milk to drink. Seek medical attention.
INHALATION: No risk

NOTE: DO NOT MIX WITH ANY OTHER CHEMICALS.

Store in a dry safe place away from children.