



Tel: +27 11 900 3633

Cell: +27 63373195

Website: www.arrow-chem.co.za

Email: sales@thearrow.co.za

HC SOEKOE cc t/a ARROW CHEM

Reg No:2002/029572/23

Vat Reg No:4600249488

Date: 2025

9 & 11 Evans Street
Alrode South
Alberton
South Africa

TECHNICAL DATA SHEET

DE-RUST

COLD APPLICATION RUST REMOVER

DE-RUST is a highly effective rust remover for removing rust and light oils and grease from ferrous metals, oxide film from aluminium, zinc galvanized iron and brass. **DE-RUST** has been designed to work most effectively at room temperature thus eliminating heating costs. **DE-RUST** imparts a light phosphate coating to ferrous metals and zinc and leaves a bright satin finish on aluminium. In all cases it improves paint adhesion. **DE-RUST** is safe on all stainless steel. **DE-RUST** is safe on paint for limited exposure, but continuous exposure may cause bleeding and deterioration of the paint surface.

PROPERTIES

- | | |
|----------------|--|
| 1. APPEARANCE: | Orange/brown liquid |
| 2. pH (10%): | N/A |
| 3. S.G.: | N/A |
| 4. STABILITY: | Stable to continued freeze/freeze thaw cycled. |

FEATURES

1. Economical to use
2. Requires no heating
3. Required no sophisticated application. Wipe on wipe off.
4. One shot metal treatment product, removes rust, oxide films light oils, and phosphates at the same time

USE DIRECTIONS

Dilute **DE-RUST** with 2-3 parts water. Apply **DE-RUST** by brush or low-pressure spray. Allow to dwell for 2-10minutes then rinse off with clean water and dry as soon as possible

SAFETY PRECUATIONS AND FIRST AID

EYES: In the case of accidental eye contact, rinse freely with water and seek medical attention urgently.
SKIN: Wash off with water. Seek medical attention urgently.
INGESTION: Give milk to drink. Seek medical attention urgently.
INHALATION: Move to fresh are
WARNING: Wear protective clothing, **DE-RUST** is acidic.

NOTE: DO NOT MIX WITH ANY OTHER CHEMICALS.

Store in a dry safe place away from children.